

C-Band Compact Klystron High Power Amplifier

The Classic Space-Saving Alternative Solution

The Compact High Power Amplifier

C-Band CKPA— provides up to 3.35 kW of power in a dual drawer package with power tracker/ power saver

Technology Reuse at its Best

Assures high reliability in a compact design based on field proven performance. Features classic klystron technology common to CPI's renowned generations of klystron high power amplifiers.

Installation Versatility

Racks and stacks two amplifiers into one cabinet in any configuration.

Useful Displays

Provides a clear, high quality, graphical display with a wide viewing angle and a sharp appearance. Clearly displays all critical functions including a comprehensive event log.

C-Band



Easy Maintenance, Easy Handling

Offers easy access to all areas of the amplifier with no harness obstructions. Separate RF and Power Supply drawers slide out from a standard rack.

Worldwide Support

Backed by over two decades of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes eleven regional factory service centers.

satcom  **division**

811 Hansen Way
P.O. Box 51625, Palo Alto, CA 94303

tel: +1 (650) 846-3803

fax: +1 (650) 424-1744

e-mail: marketing@satcom.cpii.com
www.cpii.com/satcom

C-Band

Compact Klystron High Power Amplifier

OPTIONS:

- *Motorized Channel Selector: (<1 second)*
- *Remote Control Panel*
- *Protection Switching*
- *Linearizer*
- *L-Band Block Upconverter (BUC) (Contact factory for typical performance specifications with integrated BUC)*
- *Low Phase Noise*
- *Variable Speed Blower*
- *Ethernet*

SPECIFICATIONS, C-Band CKPA

Electrical

Frequency Ranges	5.85 - 6.425 GHz; others available as options
Klystron Power Output	3.0; 3.35 kW min. (64.77; 65.44 dBm)
Amplifier Output at flange ¹	2.6; 2.9 kW min. (64.15; 64.62 dBm)
Bandwidth	45 MHz; 80 MHz available as an option.
Power Adjustability	0 to -20 dB of output with ± 0.1 dB typical resolution
Gain at Rated Power	77 dB min.
Gain Stability vs. Time	± 0.25 dB/24 hr. max. at constant drive and temperature
Gain Stability vs. Temp.	1 dB max. from 20° to 40°C; ± 2.5 dB max from 0° to 50°C (at constant drive)
Gain Slope (small signal)	0.04 dB/MHz max. over $F_o \pm 13$ MHz ($F_o \pm 18$ MHz with 80 MHz option)
Gain Variation (small signal)	0.4 dB pk-pk $\pm F_o$ 13 MHz ($F_o \pm 18$ MHz with 80 MHz option)
Input VSWR	1.25:1 max.
Output VSWR	1.30:1 max.
Load VSWR	2.0:1 max. for full spec. compliance; any value for operation without damage
Residual AM ²	-50 dBc maximum, 20 to 400 Hz -60 dBc maximum, 400 Hz to 2 kHz -80 dBc maximum, 2 kHz to 500 kHz
AM/PM Conversion (at rated power)	4°/dB maximum
Harmonic Output	-80 dBc
Noise and Spurious (at rated gain)	-135 dBW/4 kHz, 3.7 to 4.2 GHz -70 dBW/4 kHz, in passband -110 dBW/MHz, 4.2 to 40 GHz (excluding passband)
Phase Noise ²	Exceeds requirements of IESS-308/309 by -10 dB at -10 dB backoff.
Intermodulation	-29 dBc with two equal carriers at total output 7 dB below rated single-carrier output
Group Delay	In any 36 MHz band (72 MHz for 80 MHz klystron): 0.25 ns/MHz linear max. 0.05 ns/MHz ² parabolic max. 2.0 ns pk-pk ripple max.
Primary Power ³	All ratings are $\pm 10\%$, 47-63 Hz 3-phase with neutral and ground: 200 VAC w/o neutral 208 VAC 380 to 415 VAC

¹Harmonic filter can be removed as an option. Add 0.25 dB to amplifier output for units ordered without harmonic filter

²Prime power AC line unbalance not to exceed 3%. Excess imbalance may cause an increase in residual RF noise (AM, FM and PM). Phase noise increase is typically 2.5 dB / % imbalance.

³AC current harmonic content: less than 20%, primarily fifth and seventh harmonics. Harmonics must be considered when choosing UPS sources.

Electrical (continued)

Power Consumption ⁴	11.0 kW max. Typical values for the following RF output backoffs with respect to rated (power saver on): 10.5 kW @ 0 dB (rated) 10.5 kW @ -4 dB 8.5 kW @ -7 dB 7.0 kW @ -10 dB 6.0 kW @ -13 dB
Power Factor	0.95 minimum
Inrush Current, peak	180% of normal line current peak max. (first half cycle only)

Mechanical

RF Input Connection	Type N female
RF Output Connection	CPR-137F flange
RF Power Monitors	Type N female
Dimensions (W x H x D without fans and handles)	
RF Drawer	19 x 21 x 28.75 in. (483 x 533 x 730 mm)
PS Drawer	19 x 8.75 x 24 in. (483 x 223 x 610 mm)
Weight	
RF Drawer	170 lbs w/klystron (77.3 kg)
PS Drawer	90 lbs (40.8 kg)
Cooling	Forced air with integral blower and fans; separate klystron collector cooling path
Air Flow Rate, Klystron	300 cfm min., at sea level at 23°C ambient air
External Ducts Backpressure	0.5 inch water gauge total, maximum
Klystron Heat Loss ⁵	9,000 W max.
Cabinet Heat Loss (cabinet less Klystron)	1,500 W max.
Acoustic Noise	68 dBA nominal, measured 3 ft. from front of equipment

Environmental

Ambient Temperature	-10° to +50° operating; -40° to +80° non-operating
Relative Humidity	95%, non-condensing
Altitude operating:	10,000 ft. (3000 m) with standard adiabatic temp derating of 2°C/1000 ft. or 6.5°C/km
non-operating:	40,000 ft. (12,000 m)
Shock and Vibration	As normally encountered in satellite earth stations and shipping

⁴Lower power consumption can be achieved if power saver (included as standard) is employed when operating below rated output power.

⁵For 3.35kW klystron.



KEEPING YOU ON THE AIR
not up in the air

Please check CPI's web site to ensure most current data sheet.

For more detailed information, please refer to the corresponding CPI Technical Description.

Note: Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.



Communications & Power Industries

satcom division